

SPEED Pad Printing Machine



PAD PRINTING MACHINES ACCESSORIES SERVICE

The fastest clocked pad printing machine on the market

Electromechanical drive

High number of parts, highest registration accuracy

Standard Pad Printing Machines

SPEED Series

There was a need for coming up with a new pad printing machine, the basis of which opens up new target markets for us both technologically and in terms of applications. This has cut down flat-bed printing's negative distance in performance to rotary printing in terms of part output.

The result: the development of the **SPEED 40-2** pad printing machine. Its output: as many as 9,000 cycles/h in continuous run. The production quantity is max. 18,000/h printed parts (single color with a printed image size of \varnothing 37 mm). Very high true-to-register printing, precision contours and photo and line images.

The **SPEED** is a built-in execution, suitable for any kind of clocked, linear or rotary transfer systems. Thanks to its integrable misprint device there is no stopping of the machine in the absence of a workpiece.

The power costs are low in comparison to the cycle number (part output). The **SPEED 40-2** is a fast shortstroke machine of a new series of pad printing machines.

No other pad printing machine on the market offers these benefits.



SPEED 40-2



SPEED 40-2
Housing cover made of stainless steel

SPEED Series

Focus on productivity



With pad printing
it becomes dosable

Technology

SPEED Series

SPEED 40-2		SPEED 40-2	SPEED 40-2	SPEED 40-2	SPEED 40-2
Integrated model	Item No.	01 06 10	01 06 11 ²⁾	01 06 12	01 06 13
Misprint device		optional	optional	optional	optional
Single cycle		yes	yes	yes	yes
Multiple printing		yes	yes	yes	yes
Continuous run		yes	yes	yes	yes
Piece counter		–	yes	–	–
Variable speed control		external	yes	external	–
Number of cycles/hour	max.	1500–9000	1500–9000	1500–9000	1500–9000
Ink/doctoring cup	Ø mm	2x Ø 42	2x Ø 42	2x Ø 42	2x Ø 42
Variable doctoring contact pressure		no	no	no	no
Cliché size	mm	150 x 110	150 x 110	150 x 110	150 x 110
Print image size max.	Ø mm	2x Ø 37	2x Ø 37	2x Ø 37	2x Ø 37
Pad stroke onto workpiece	mm	60	60	60	60
Pad stroke onto cliché	mm	23	23	23	23
Pad installation height max.	mm	60	60	60	60
Force of pressure per pad/machine	N	270/550	270/550	270/550	270/550
Drive (see below)		electromechanic	electromechanic	electromechanic	externally driven
Connected load	kW	0,6	1,0	1,0	–
Power supply	V/phase	400V/3/N/PE	400V/3/N/PE	400V/3/N/PE	–
Interface		–	D-SUB 37-pole	–	–
Power frequency	Hz	50–60	50–60	50–60	–
Control		–	PLC	–	–
Control voltage	V/DC	–	24	24	–
Prefuse	A	16	16	16	–
Pneumatic supply fine filter 5 µm	bar	6 ¹⁾	6 ¹⁾	6 ¹⁾	6 ¹⁾
Air consumption/cycle	NL	0,1 ¹⁾	0,1 ¹⁾	0,1 ¹⁾	0,1 ¹⁾
Width	mm	297	297	297	297
Depth	mm	430	430	430	430
Height	mm	592	592	592	592
Weight	approx. kg	38	38	38	38

1) if option misprint device is used 2) stand-alone

Drive Description		Drive with AC asynchronous motor and resolver, without controller; without connecting cable; without control cabinet	Drive with AC asynchronous motor and frequency converter; connecting cable (5 m) with plug connection at the machine; with control cabinet	Drive with AC asynchronous motor and servo controller; connecting cable (5 m) with plug connection at the machine; without control cabinet	Without motor, externally driven (input shaftgear)
-------------------	--	--	--	--	--

Standard Pad Printing Machines

SPEED Series

SPEED 40-2

Automation with 4-fold use
36 000 parts/h



SPEED 40-2

Automation for small parts
with rotary index table



Scope of supplies

- Ink/doctoring cups
- Hold-down bridge client-specific version
- Pad bridge client-specific version
- Assembly table
- Gripping tongs
- Printing pads
- Tools and accessories set
- Technical documentation

Accessories & Options

- Machine stand made of aluminium profiles
- Frame made of steel, closed, with angle table
- Aluminium cross table for the positioning of jigs
- Mounting plate for jig
- Misprint device
- Overhead model

TAMPOPRINT® AG
Lingwiesenstraße 1
70825 Korntal-Münchingen
GERMANY

Tel. +49 7150 928-0
Fax +49 7150 928-400

info@tampoprint.de
www.tampoprint.de

TAMPOPRINT® IBERIA S.A.U.
Polígono Industrial Martorelles
C/ Sant Martí, s/n (entre Gorgs y Mogent)
08107 Martorelles (Barcelona), SPAIN

Tel. +34 93 2327161
Fax +34 93 2471500

tampoprint@tampoprint.es
www.tampoprint.es

TAMPOPRINT® INTERNATIONAL CORP.
1400 26th Street, Vero Beach
FL 32960
USA

Tel.+1 772 778-8896, 800 810-8896
Fax +1 772 778-8289

sales@tampoprint.com
www.tampoprint.com



Technical Data
tampo.link/speed

The reproduction of trademarks and brands used in this brochure, even if not explicitly expressed, does not justify the assumption that such names or symbols may be considered as free as defined by the Trademark Act and may therefore freely be used. The rights are the property of the respective owner. TAMPOPRINT products are permanently updated to keep pace with the latest technological developments. For this reason, figures and descriptions are non-binding. Our machines are manufactured based on the currently valid European Machinery Directives as well as the European product standards EN 1010 - 1 and EN 1010 - 2.

Copyright © 2019 TAMPOPRINT AG. Subject to technical changes and other modifications.

All locations are certified ISO 9001:2015

04/2019