

## APPLICATION INSTRUCTIONS

# Graffiti

Printable flex film with the best compromise between cuttability and touch.  
Soft, elastic, easy to cut and with a very good wash-fastness.

### FEATURES:



**PU  
water-  
based**



**60µ**



**Cotton, polyester,  
blended fabrics..**  
Also suitable for most water  
repellent coated textiles.



**EcoSolvent (incl. TrueVis),  
Solvent, Latex**



1. Print and cut

### CUTTING CONDITIONS:



**Blade  
30 - 45°**



**low/  
medium**



**30 - 40 cm/s**



2. Weed design

### TRANSFER CONDITIONS COTTON:



**150°C**



**10 s**



**medium/  
high**



**Hot peel**



**60°C**



3. Apply tape

### TRANSFER CONDITIONS POLYESTER:



**125°C**



**10 s**



**medium/  
high**



**Hot peel**



**60°C**



4. Transfer, remove tape,  
done !

Printing profiles at [www.seftextile.com](http://www.seftextile.com)

Recommended transfer tape: FlexTape

Drying time: Depending on ink and conditions 1 - 6h

For small designs, it can be useful to first apply the tape over the whole surface and then to weed it from the back.

### ► PACKAGING

50 cm	25 m & 10 m
75 cm	25 m & 10 m

Store in a cool and dry place; protect against the influence of light when stored. We recommend not to exceed a storage period of 12 months. The technical specifications rest on extensive tests and technical research. Due to the variety of possible influences during refinement, and use, the specifications should be viewed as reference values. We recommend a suitability test on the original material. A legally binding warranty of specific characteristics cannot be derived from our specifications.