


# BLAZECUT


## Heat transfer flex-film

> for plotter-cutting


Cut 




Silver




Gold




Pink




Purple



Light Blue



Blue



Rainbow



Diamond



If you want something special, **BlazeCut** is the right choice for you! The dazzling Holo effect brings something special to your designs. With its sticky polyester carrier **BlazeCut** is easy to work with and has an excellent 40 °C wash fastness



Si vous voulez quelque chose de spécial, **BlazeCut** est le bon choix pour vous ! L'éblouissant effet Holo apporte quelque chose de spécial à vos créations. Avec son support polyester collant **BlazeCut** est facile à travailler et possède une excellente résistance au lavage à 40 °C.



Wenn es etwas Besonderes sein soll, liegen Sie mit **BlazeCut** genau richtig! Der schillernde Holo-Effekt bringt Ihren Designs das besondere Etwas. Mit seinem rückklebrigen Polyesterträger ist **BlazeCut** leicht zu verarbeiten und besitzt eine hervorragende 40 °C Waschechtheit.




Manufacturing processes and related products are protected by existing patents :  
FR 97 12921; EUR 98 402 542.9 ; US 6.224.707 ; FR 98 12862 ; EUR 99 402 398.4 ; US 6.249.297 ;  
FR 04 08625 ; FR 05 05379 ; FR 05 05380 ; international extensions and new applications pending.

# BLAZECUT

## Heat transfer flex-film

> for plotter-cutting

Cut 



1




Scan or create a digital vector image.

2



Cut a mirror-image of your design on a plotter-cutting machine.

3



Apply with an electric press

### COMPOSITION

Base	Hotmelt film (polyurethane)
Thickness	100 µ



### TECHNICAL INFO

Washing fastness	up to 40°C (104°F) u
Transfer	8 seconds - 165 °C (330 °F) - Medium / high pressure Please note that waiting 20 seconds to remove the liner after pressing will give a shinier finish

### APPLICATION

Cotton
Poly/Cotton
Polyester

### PACKAGING

	
50 cm [19,7"]	25 meters [27,3 yd]



110 Bd Denis-Papin - 53000 LAVAL - France

Tél : 33 (0) 2 43 53 36 48

Fax : 33 (0) 2 43 67 11 78

Email : [contact@sef-france.com](mailto:contact@sef-france.com)

[www.seftextile.com](http://www.seftextile.com)