

7 Rue Edouard Garet 42 160 Andrézieux

anco

téléphone 0033 (0)4 77 42 65 90 email info@cfpflex.com

6/3/2020

Date

France

DATA SHEET

LIBERTY LASER Laser printable TRANSPARENT A4 / A3 film **PRODUCT** CLEAR A for white or clear textile CODE L401 A (box of 100 sheets) DESCRIPTION Heat-adhesive film on polyester selfadhesive carrier Printable film: 60 microns THICKNESS +/-5% Polyester carrier: 120 microns. 1. Text, image, photo must be printed mirrorwise. 2. Use the Bypass feeding (manual feeding) of the printer, on Heavy Mode setting. **USER'S GUIDE** 3. If wanted, cut out the contours using a plotter with an optical eye function, and weed. Add a white sheet between the cutting mat and Liberty Laser in order to optimise the cutting crop marks spotting. Set up the blade to cut only the print film, and not the polyester carrier, then weed. 4. Put the printed and weeded face directly on the textile, protect the sheet with baking paper. 5. After a first heatpressing at 160°C / 30 seconds, peel the carrier after cooling, and press a second time at 160°C / 30 seconds, while protecting the print with baking paper. Pressure: 5 bars (70 PSI) on automatic press, maximum pressure on manual press. WASHING TEMPERATURE TEXTILES Cotton - Polyester - Polycotton - Nylon (to be tested before use). 1. Very quick and cost saving to print with a standard CMYK laser printer 2. A professional soft touch, simple to transfer with one format only to use 3. A high quality full colors print with no rasterisation/RIP sofware 4. Great scalability: unit or high volume personalisation 5. Easy to get small details 6. Possibility to cut out the contours thanks to a plotter with an optical eye function **ADVANTAGES** 7. Transparent carrier allows to place the image accurately on textile. 8. Universal thermoadhesive with excellent proven bonding on most textiles 9. Withstand many washing cycles up to 60°C. 10. Elastic and strong film, doesn't wrinkle after washing. 11. Ecofriendly, water based, solvent and PVC free polyurethane. 12. Low carbon profile manufacturing: all operations made under one roof 13. 100% made in France, out of european raw materials. 14. Last generation machines and exclusive manufacturing process, ensuring competitive prices 1. Wait 24 hours before washing. **FURTHER** 2. Do not use bleach or other aggressive chemical agents. RECOMMENDATIONS 3. Iron from inside. 4. Store our products in a tempered and dry room, protected from direct sun rays. **SAFETY** Inert components, REACH compliant, without PVC, plastifiers, heavy metals, VOC, according to Oekotex Standard 100 Class 1. RESUBLIMATION Do not use on sublimated printed polyester. This document is likely to be modified without notice. Please take contact with our commercial department.