FOTECFOIL 7800

SPT SALES + MARKETING GMBH

FOTECO REMCO SAATI

Inkjet Clear Film for Computer-to-Film (C-t-F) Application

1. DESCRIPTION

- FOTECFOIL 7800 has excellent dimensional stability
 and is therefore most suitable for the different
 production of films. Such films need the highest
 demands for the exposure of screen process stencil
 materials with FOTECOAT emulsions or FOTECAP
 capillary films. In addition they can be used with
 the indirect film system FOTECFILM.
- FOTECFOIL 7800 is coated on the print side
- The necessary density to expose screen process stencils can be reached with a correct linearization of the inkjet printers.
- FOTECFOIL 7800 can be used for the production of positive or negative films and for the colour separation in the exposure process of screen process stencil materials.

2. CHARACTERISTICS

- · Goode humidity resistance
- · Fast ink drying
- · Good definition and density
- The UV-denisty depends on the RIP installations, the ink system and the spectral characteristics of the densitometer.
- · The dot reproduction depends on the RIP
- FOTECFOIL 7800 is anti-static

| | FOTECFOIL 7800 |
|----------------------|----------------------|
| Carrier | Clear Polyester Foil |
| Carrier Thickness | 0,1 mm |
| Print Side Thickness | 0,026 mm |
| Coating | For Inkjet Printers |
| Print Side | Slighty Matt Surface |

3. COMPATIBILITY PRINTERS

- FOTECFOIL 7800 is suitable for most inkjet printers which use water based inks.
- Dye or pigment ink systems are usable but not oil- or solvent based inks.

4. HANDLING

- Room temperature: 15 bis 30°C
- Relative humidity: 30 % bis 70 %
- Pre-conditioning during a period of 24 hours within the printing environment is recommended.
- Fingerprints on the printing side are to be avoided.

5. STORAGE

- Store at a cool and dry place. Storing time one year for unopened packages
- Once the package is opened store at room temperature of 15 bis 25° C and at humidity of 30 bis 60 %.

6. PACKAGING

Roll length: 30 m standard

Core: 3-Zoll (76 mm); The end parts of the roll holding are supplied together with the Epson printers.

Roll widths FOTECFOIL 7800:

- 35,5 cm
- 17"/43,1 cm
- 24"/61 cm
- 36"/91,4 cm

Formats sheets FOTECFOIL 7800:

- A4 (21 cm x 29,7 cm)
- A3 (29,7 cm x 42 cm)



Our technical advice whether spoken, written, or through test trials corresponds to our current knowledge to inform about our products and their use. It is not meant as an assurance for certain properties of the products nor their suitability for each application. You are, therefore, obliged to conduct your own tests with our supplied products to confirm their suitability for the desired process or purpose. The selection and testing of products for specific final application is exclusively your responsibility.

SPT Sales + Marketing GmbH ein Unternehmen der SAATI Group Kurpfalzring 100A, 69123 Heidelberg Telefon: +49 (0) 62 21 | 77 876-27 E-Mail: spt@spt-gmbh.com Web: www.spt-gmbh.com