VARIOWASH 2882

SPT SALES + MARKETING GMBH

FOTECO REMCO SAATI

Screen Cleaner, flash point 62°C

1. PROPERTIES

VARIOWASH 2882 is a screen cleaner and mesh opener with mild odour and a flash point of 62°C. The effective multi-purpose solvent blend is developed for removing of almost all graphics, electronics, glass and textile screen printable ink systems (solvent- and UV curing), tools and squeegees.

The well-balanced formulation of the slow volatile screen wash ensures gentle treatment of all direct/indirect emulsions and capillary films as well as 2-component screen adhesives and has no negative effect on their solvent resistance when handled correctly.

VARIOWASH 2882 contains aromatic hydrocarbons but not any chlorinated solvents or toxic organic substances that are classified in the legislation for hazardous substances and list of maximum workplace concentrations as damaging to embryos or genetic substance.

Safety and pollution related data can be obtained from the respective SDS according to guidelines 1907/2006/EC.

2. APPLICATION

VARIOWASH 2882 is developed for application in wash out basins and automatic screen washing units. Because of the slow volatility, the use for manual screen cleaning and mesh opening is limited.

The screen cleaner has a flash point of 62°C and fulfils the requirements of explosion protection for screen printing and cleaning in accordance with the regulation of EN 1010 = Safety of machinery - Safety requirements for the design and construction of printing and paper converting machines. The high flash point eliminates the need for explosion proof tools in working areas.

If used in automatic screen washing machines the cleaner can be recycled by vacuum distillation. For trouble-free operation of washing and distillation equipment, it is particularly important to regularly check the plant functions and the quality of the distillate and the utilized solvents for optimum mode of operation.

The well trained **SPT** service technicians offer competent and customer friendly assistance, fast and reliable.

3. PACKAGING - STORAGE

VARIOWASH 2882 is packaged in standard 1, 5 or 20 L tin cans and in 58 L or 200 L drums. The cleaner has to be stored in a dry and against frost-protected place. Do not expose to direct sun light.



Our technical advice whether spoken, written, or through test trials corresponds to our current knowledge to inform about our products and their use. It is not meant as an assurance for certain properties of the products nor their suitability for each application. You are, therefore, obliged to conduct your own tests with our supplied products to confirm their suitability for the desired process or purpose. The selection and testing of products for specific final application is exclusively your responsibility.

SPT Sales + Marketing GmbH ein Unternehmen der SAATI Group Kurpfalzring 100A, 69123 Heidelberg *Telefon:* +49 (o) 62 21 | 77 876-27 *E-Mail:* spt@spt-gmbh.com *Web:* www.spt-gmbh.com