# **VARIOCLEAN S 4379**

**SPT** Sales + Marketing GmbH

#### FOTECO REMCO SAATI

# Screen Cleaner, biodegradable, flash point 80°C

### 1. PROPERTIES

**VARIOCLEAN S 4379** is a low odour screen cleaner with a flash point of 80°C. The extremely effective multi-purpose solvent and wetting agent blend is developed for removing of almost all graphics, textile screen printable ink systems (solvent-, water-based and UV curing) and water removable glass printing inks from screens, tools and squeegees.

The well-balanced formulation of the slow evaporating and low VOC screen wash ensures gentle treatment of all direct/indirect emulsions and capillary films as well as 2-component screen adhesives and has no negative effect on their solvent resistance when handled correctly.

**VARIOCLEAN S 4379** is readily biodegradable and contains no aromatic hydrocarbons, chlorinated solvents or toxic organic substances that are classified in the legislation for hazardous substances and list of maximum workplace concentrations as damaging to embryos or genetic substance.

Safety and pollution related data can be obtained from the respective SDS according to guidelines 1907/2006/EC.

## 2. APPLICATION

The application of **VARIOCLEAN S 4379** is carried out mainly for use in wash out basins and automatic screen washing systems.

The flash point of 80°C eliminates the need for explosion-proofed infrastructure in working areas.

For removing of plastisols, water based textileand glass inks as well as sublimation inks the cleaner can be diluted 1: 1 until 1: 5 with tap water.

The screen cleaner water mix has an extremely long operational effectiveness and the ink contaminated cleaner solution can be re-used by filtration, sedimentation and/or flocculation. Detailed information regarding the possible recycling methods is stated in the relevant **SPT** data sheets.

The well trained **SPT** service technicians offer competent and customer friendly assistance, fast and reliable.

#### 3. PACKAGING - STORAGE

VARIOCLEAN S 4379 is packaged in standard 1, 5 or 20 L tin cans and in 200 L drums. The cleaner has to be stored in a dry and against frost-protected place. Do not expose to direct sun light.



Our technical advice whether spoken, written, or through test trials corresponds to our current knowledge to inform about our products and their use. It is not meant as an assurance for certain properties of the products nor their suitability for each application. You are, therefore, obliged to conduct your own tests with our supplied products to confirm their suitability for the desired process or purpose. The selection and testing of products for specific final application is exclusively your responsibility.