

VARIOSTRIP 5228

Decoating Concentrate 1:25/30

1. PROPERTIES

VARIOSTRIP 5228 is a water soluble decoating concentrate developed for the manual and automatic rapid removal of direct emulsions, direct/indirect, capillary from all types of polyester, nylon and metal fabrics.

It is not formulated for removal of indirect gelatin films. Therefore, we recommend our **VARIOSTRIP 5877** decoating concentrate, based on enzymes.

VARIOSTRIP 5228 is corrosive and supplied as an easily dilutable, biodegradable, cost effective liquid.

The decoating working solution is not hazardous when used with reasonable standards of industrial hygiene and safe working practice.

Safety and pollution related data can be obtained from the respective SDS according to guidelines 1907/2006/EC.

2. APPLICATION

For manual use dilute

1 part of the VARIOSTRIP 5228 concentrate with 25 - 30 parts of water

and apply the working solution with a wet medium stiff brush from both sides. Let the screen stand for 30 - 90 seconds. Wash away the stencil with a high-pressure water spray from bottom to top. It is important to ensure that the screen is free from ink residues before decoating.

Under no circumstances should the stencil remover be allowed to dry onto the screen, as this can result in a permanent stencil.

The mixing ratio for automatic use depends on the type of equipment. The working solution will not block or corrode stainless steel or polypropylene based nozzles in the automatic decoating unit. Use in accordance with the recommendations of the machine manufacturers and **SPT**.

3. PACKAGING - STORAGE

VARIOSTRIP 5228 is packaged in standard 1, 5 and 20 L plastic cans plus 200 L plastic drums. The decoating concentrate has to be stored dry and protected against frost. Keep away from heat and do not store near combustible materials. Keep container closed when not in use.

Our technical advice whether spoken, written, or through test trials corresponds to our current knowledge to inform about our products and their use. It is not meant as an assurance for certain properties of the products nor their suitability for each application. You are, therefore, obliged to conduct your own tests with our supplied products to confirm their suitability for the desired process or purpose. The selection and testing of products for specific final application is exclusively your responsibility.

SPT Sales + Marketing GmbH
ein Unternehmen der SAATI Group
Kurfalzring 100A, 69123 Heidelberg
Telefon: +49 (0) 62 21 | 77 876-27
E-Mail: spt@spt-gmbh.com
Web: www.spt-gmbh.com



Eine Marke der SPT