

VARIOSPRAY DP 1

Stencil Developing Gun

1. APPLICATION

The stencil developing gun **VARIOSPRAY DP 1** fulfills all requirements for an effective washing out of unexposed emulsions and capillary films.

The unique and high efficient 3-nozzle system guarantees a perfect print shoulder and edge definition. The special effect results from the acceleration and fine distribution of the spray water, associated with a significant tap water saving up to 60%.

Required tap water pressure should be at least 2 to 3 bar. When used in conjunction with a high pressure device, the working pressure should be adjustable from 5 to 15 bar.

2. TECHNICAL DATA

According to the requirements, the items of the gun are made of lightweight and high quality, organic solvent resistant epoxy plastic and other rustproof materials.

Nozzles, nozzle head, spray pipe and shut-off can be supplied separately as spare parts. Following hose-coupling parts are available:



High pressure screw joint



1/2 inch hose nozzle



brass reduce screw 1/2 inch thread



Eine Marke der SPT

Our technical advice whether spoken, written, or through test trials corresponds to our current knowledge to inform about our products and their use. It is not meant as an assurance for certain properties of the products nor their suitability for each application. You are, therefore, obliged to conduct your own tests with our supplied products to confirm their suitability for the desired process or purpose. The selection and testing of products for specific final application is exclusively your responsibility.

SPT Sales + Marketing GmbH
ein Unternehmen der SAATI Group
Kurfalzring 100A, 69123 Heidelberg
Telefon: +49 (0) 62 21 | 77 876-27
E-Mail: spt@spt-gmbh.com
Web: www.spt-gmbh.com