

## INK COMPATIBILITY

	ClearFlex Matte	Tattoo	Graffiti	MoZaic	ClassicPrint	Tattoo Nylon	Tattoo SBB Maxima	FiberPlus	SubliFlock	EcoPrint	Fiberstic
<b>Solvent</b>	✓	✓	✓	✓	✓	✓	✓			✓	✓ *
<b>Eco Solvent</b>	✓	✓	✓	✓	✓	✓	✓			✓	✓ *
<b>Roland Truevis</b>		✓		✓	✓		✓				✓ *
<b>Latex</b>			✓	✓	✓	✓	✓				✓ *
<b>UV Mimaki LUS 170</b>		✓		✓	✓	✓	✓				✓ *
<b>UV Roland UV2</b>				✓	✓	✓	✓				✓ *
<b>Pigment</b>											✓ *
<b>Sublimation</b>								✓	✓		
	60µ	60µ	60µ	75µ	140µ	70µ	100µ	400µ	500µ	450µ	450µ
	PU	PU	PU	PU	PVC	PU	PU	PU	PU	PVC	PVC
<b>Surface</b>	Matt	Matt	Matt	Matt	Matt	Satin	Matt	Flock	Flock	Flock	Flock
<b>Application with tape</b>		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
<b>Application without tape</b>	✓			✓	✓	✓	✓	✓	✓	✓	✓
	160 °C, 15s	165 °C, 17s 165°C,7s+15s	150 °C, 10s 125 °C, 10s* *Polyester	150 °C, 5s 130 °C, 10s	165 °C, 17s	115 °C, 15s	135 °C, 10s	165 °C, 17s	165 °C, 17s	165 °C, 17s	self-adhesive
	60 °C	40 °C 60 °C	60 °C	60 °C	60 °C	40 °C	60 °C	60 °C	40 °C	60 °C	
										Class I	

\* depending on the desired fastness