

Cotton/Poly Blend

50/50, other cotton blends

Quick White - 11835HT

- Easy printing, fast flash, low after-tack
- ▶ Superb fiber mat down
- Super smooth and high opacity
- Optically bright
- ▶ Soft hand

White Buffalo - 11815HT

- Easy printing on variety of meshes
- Good flash properties, low after-tack
- ▶ Good fiber mat down
- Super smooth and high opacity
- ▶ Soft hand

Bright Tiger - 11480HT

- Easy printing on variety of meshes
- ▶ Good flash properties
- Matte finish
- ► Good opacity

XTreme White - 11999XW

- Designed for fine mesh printing
- ▶ Excellent underbase properties
- ▶ Fast flash

White Inks



Experience has shown that, when it comes to white inks, there is no "magic in a bucket." The right white must be chosen for a specific job and that's exactly why Wilflex[™] offers you such a wide variety of white inks. **Wilflex White Inks** are creamy, fast-flashing and result in excellent opacity. You will find that only Wilflex offers so many options, ensuring that you'll always find the right ink for a particular application.

www.wilflex.com/pib to access all Wilflex[™] Product Information Bulletins

Cotton

For 100% cotton fabrics

Sprint White - 11335WHT

- Easy printing, fast flash, low after-tack
- Superb fiber mat down
- Super smooth and high opacity
- Optically bright
- Soft hand

Artist Plus - 11122WHT

- Fast flash, low after-tack
- Excellent fiber mat down
- Matte finish
- Soft hand
- Smooth finish

Polyester

For 100% polyester fabrics

Poly White - 11117WHT

- Superior bleed resistance
- No odor, non-peroxide
- Great opacity
- Easy printing

MVP LB White - 11195MVP

- Peroxide-based chemistry
- Excellent fiber mat down
- Good bleed resistance
- ▶ Compatible with 100% cotton fabrics

Nylon

For 100% nylon fabrics

Pennant - 11000PEN

- Easy manual and auto printing
- ▶ Micromesh, porthole, dazzle cloth
- ▶ Super adhesion and durability
- ► Gloss finish

One Step Nylon - 11000OSN

- Superior adhesion qualities
- Untreated nylon fabrics
- ► Coarse and fine denier fabrics
- ▶ Hugger Catalyst for extra adhesion

Specialty

Special applications

SSVFF - 11000SSVFF

- Fast fusing/lower cure temp
- ► Heat sensitive and high stretch fabrics

NuPuff - 11000NPF

- ► Durable puff white ink
- Best results in lower mesh counts

NuPuff - 11010NPF

- ► Durable puff white ink
- ► Low bleed properties

Brittle White - 11000BB

- Cracking surface with applied pressure
- Create worn or distressed look
- ► Very durable, hard finish

USA

PolyOne 8155 Cobb Center Drive Kennesaw, GA 30152 Tel: 770.590.3500 Tel: 800.326.0226 Fax: 678.290.2749

England PolyOne Corp. UK Ltd. Everite Road Widnes Cheshire, WA8 8PT United Kingdom Tel: +44 0151 495 4400 Fax: +44 0151 495 1853

email: techserviceswilflex@polyone.com

China PolyOne China

No. 1, QiHang Industrial Park Haoxiang Road, Shajing Town Baoan District, Shenzhen 518104 Guangdong, China Tel: +86 755 2969 2888 Fax: +86 755 2969 2999

Turkey PolyOne Turkey [Kitelli Organize Sanayi Bölgesi Turgut Özal Cad. No:103 Küçükçekmece, İstanbul, Turkey Tel: +90 (212) 549 22 56 Fax: +90 (212) 549 22 41

wilflex.com

PolyOne. ©2007 PolyOne Corporation All Rights Reserved. Wilflex™ inks by PolyOne.

Product Literature :: Wilflex White Inks 06.05.08 Rev.C