


We invite you to be a
happy customer

A machine is more than just
a machine. Oftentimes, it has
a complicated construction
that at the same time must be
effective, durable and easy to
handle and install, and use as
few resources as possible.

Groenlund Machine Works
manufactures functional, prac-
tical and economic machines
in high-tech Scandinavian de-
sign. Several of our machines
are industrial classics.

Our  not only stands for
Groenlund and our many years
of experience, but also for our
good quality. Therefore we are
confident that you will also be
a satisfied Dane customer.



screen printing:
a difficult work process –
labour intensive

+

dane machines:
automating work process –
saving labour

equals:
greater job satisfaction,
higher profits and
a cleaner environment

Contact: dane 

Groenlund machine works ltd.

43 - 47 Jernholmen

dk – 2650 hvidovre

phone +45 3234 6000

fax +45 3234 6010

e-mail: gggroup@ggroup.dk

www.ggroup.dk



dane · drum · pump

screen accessories



dane - drum pump professional

Drum og reservoir emptying or filling is accomplished quickly, efficiently and safely with the dane portable drum pump. Utilizing the dane drum pump, drums or reservoirs are filled or emptied without messy spills and splashes - operator contact or exposure to potential harmful materials is avoided. The dane drum pump is designed with the user in mind i.e.: compact, impact-resistant motor, comfort-grip handle with easy access to on/off switch.

The dane drum pump has a proven design. Strict process and quality controls assure consistency of product quality. The dane drum pump is CE-marked.

A typical pump user will find the dane drum pump a reliable replacement for pouring, using hand pumps or diaphragm pumps. The dane drum pump is easier to use, more mobile, less costly to operate and easy to clean and maintain.

The dane drum pump is a light weight alternative to handle light viscosity chemicals. The dane drum pump is designed to fit in drums and reservoirs with small openings.

- Unique Lifting compressor design
- Strong and solid construction
- Mild corrosives and solvents resistant gaskets
- Chemicals with a minimum flash point of 133°F / 56°C
- 65 liter per minute
- Low noise - only 78db
- Stainless steel tube - AISI304
- Tube 37" / 940mm, Ø50mm
- AC motor, 50-60 Hz, 220/240 or 115 VAC
- Impact resistant housing with integrated handle

Distributor: